



### SIMPLICITY

Top arc indication ensures easy adjustments from 40° - 360°. Five interchangeable nozzles available.

## **CONVENIENCE**

Part- and full-circle arcs in one sprinkler offer convenience and reduce inventory requirements. Ratcheting riser provides easy final arc adjustment.

## VERSATILITY

Fills in that hard to cover 18' to 30' gap between spray heads and rotors.



## **SPECIFICATIONS**

# Mini 8 Series Sprinklers

## **SPECIFICATIONS**

#### Lawn Pop-Up

- Radius: 20' 35' (6,1 10,7m)
- Flow Rate: 0.80 3.40 GPM (3,0 - 11,5 LPM)
- Recommended operating pressure: 30-50 psi (2,4 - 3,5 Bar)
- Maximum operating pressure: 60 psi (4,4 Bar)
- Body Diameter: 1 <sup>3</sup>/<sub>4</sub>" (44mm)
  Cap Diameter: 2 <sup>1</sup>/<sub>4</sub>" (57mm)
- Height: 6" (150mm)
- $\frac{1}{2}$ " (13mm) threaded NPT inlet
- **Pop-up to nozzle:** 3 <sup>3</sup>/<sub>4</sub>" (95mm)

#### **Nozzle Performance**

• Lawn Pop-up Apex @ 40 psi (2,8 Bar)

	25°		
Nozzle	Max. Height of Spray		
0.75	3′11″ (0,95m)		
1.0	5′1″ (1,55m)		
1.5	6′7″ (2,04m)		
2.0	7'6" (2,32m)		
3.0	7'6" (2,32m)		

## **FEATURES**

#### **Operational**

- Pressure activated seal and robust trip mechanism for enhanced reliability
- Trajectory: 25°
- Two-Year Warranty

#### Installation

- Five interchangeable nozzles (comes preinstalled with à 1.5 nozzle) to cover varying flow requirements
- Stainless steel radius adjustment screw allows up to 25% reduction
- Ratcheting riser for easy arc adjustment
- 1/2"' inlet covers smaller radius requirements
- Optional check valve holds back 8' elevation change



Arc Scale

#### Arc Adjustment

Use slot screwdriver to turn. Read arc change on the arc scale as the screwdriver is turned. The arrow points to the arc degrees.

## Specifying Information

MINI8 4P XX XX				
Description	Body	Nozzle	Optional	
Mini 8 –Mini 8 Rotor	4P – Lawn Pop-up	7575 10 - 1.0 15 - 1.5 20 - 2.0 30 - 3.0	CV – Check Valve	
Exar	nple: A Mini 8 Series Spri would be specified as:			