

Count on it.

ROTORS

T5 Series Rotor

A multi purpose, basic featured rotor for all standard residential and commercial uses.



Even with more time between cuttings— One head stands tall!

Competition "B"

Competition "B"

INNOVATIVE

In-ground profile of any standard 4" pop-up, but delivers a full 5" pop-up.

EXTRA PERFORMANCE

Highly engineered nozzles deliver maximum irrigation efficiency from a nozzle tree of 8 Standard and 4 low angle nozzles.

VALUE

Part- and full-circle sprinkler in one head with optional check valve.




SPECIFICATIONS

T5 Series Rotor

NOZZLES

Geometry on the face of the nozzle creates breakup.





EXTENSIVE TESTING

T5 nozzle efficiency was developed using SPACE™ calculations

Features & Benefits

5" Pop-Up

 Easily replaces many competitive units in the same footprint but delivers an extra inch of pop-up

Standard Rubber Cover

 The top of the sprinkler is covered with a heavy duty rubber cover to minimize impact injuries and reduce liability

Nozzle Tree

 The T5 comes with a full nozzle tree of 8 standard nozzles (25°) and 4 low angle nozzles (10°)

Optional Check Valve

 An optional check valve is available with a hold back strength of 7' of elevation change

Top Adjust Arc Set

- The T5 can be set between a minimum arc set of 40° and a full circle set of 360°
- Arc changes are made from the top of the sprinkler while popped up or down by using a small slotted screwdriver.

Specifications

Model	Description
Model	Description
• T5P	5" Lawn Pop-up w/o check valve
Dimensions	

Dimensions

Body Diameter: 2 ¼"
Cap Diameter: 2 ½"
Height: 7 ½"

Operating Specifications

• Radius: 25'-50'

• Flow Rate: .76 – 9.63 GPM

 Recommended Operating Pressure Range: 25-65 PSI (maximum – 75 psi)

• Trajectory: 25° standard, 10° low angle

Pop-up to nozzle: 5"
Inlet: ¾" NPT

• Factory installed with a #3.0 nozzle

Options Available

• Check valve

Warranty

Two years

Specifying Information—T5 Sprinkler

T5P-XXXX-COM-E							
Description	Body	Nozzle		Optional	Effluent		
T5P	P	XXXX		СОМ	<u>E</u>		
T5 Sprinkler	P—5" Lawn Pop-up S—Shrub* HP—High- pop* *Available Summer 2008	15—1.5 GPM 20—2.0 GPM 25—2.5 GPM 30—3.0 GPM 40—4.0 GPM 50—5.0 GPM 60—6.0 GPM 80—8.0 GPM	10LA—1.0 GPM 15LA—1.5 GPM 20LA—2.0 GPM 30LA—3.0 GPM	COM—Check- O-Matic	E—Effluent		

Example: A T5 pop-up sprinkler with a 2.5 GPM nozzle, would be specified as: T5P-25

